

Industry Equals



RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including UL and ETL.

Product Description	Specifications	Applications	Color Code Chart
Tin copper conductors, PVC insulation, short overall twist lengths, Filler as required, Shielded tape with drain wire, Gray PVC jacket. Sequential footage marking.	Conductor Tinned Copper Insulation Equal to competitor Jacket Equal to competitor NEC Articles 800 CMR 14-12 AWG CL2 Voltage Rating 300 V Temp. Rating 75°C	<ul style="list-style-type: none"> • Security System • Intercom Systems • Sound/Audio System • Power-Limited Controls 	*Equal to competitor

PART NO.	AWG/ COND	STRAND	OUTER JKT THICKNESS		NOMINAL OD		AVAILABLE PUT-UPS	SHIP WT / 1M'
			INCH	mm	INCH	mm		
22002TSD <i>Equal to Belden 8761</i>	22/2	7x30 TC	.025	.64	.175	4.44	500'/1000'	18
22003TSD <i>Equal to Belden 8771</i>	22/3	7x30 TC	.033	.84	.199	5.05	500'/1000'	24
22022TSD <i>Equal to Belden 8723</i>	22/4	7x30 TC	.025	.64	.160	4.06	500'/1000'	19
22033TSD <i>Equal to Belden 8777</i>	22/6	7x30 TC	.025	.64	.273	6.93	500'/1000'	42
20002TSD <i>Equal to Belden 8762</i>	20/2	7x28 TC	.028	.71	.204	5.18	500'/1000'	23
20003TSD <i>Equal to Belden 8772</i>	20/3	7x28 TC	.033	.84	.218	5.54	500'/1000'	32
318004SD <i>Equal to Belden 9418</i>	18/4	19/30 TC	.035	.89	.245	6.22	500'/1000'	49
21803TSD <i>Equal to Belden 8770</i>	18/3	16x30 TC	.033	.84	.246	6.25	500'/1000'	39
21802TSD <i>Equal to Belden 8760</i>	18/2	16/30 TC	.028	.71	.222	5.64	500'/1000'	26
21602SD <i>Equal to Belden 8719</i>	16/2	19x29 TC	.032	.81	.313	7.95	500'/1000'	49
14002TSD <i>Equal to Belden 8720</i>	14/2	19x27 TC	.035	.89	.355	9.02	500'/1000'	71
21202SD <i>Equal to Belden 8718</i>	12/2	19x25 TC	.040	1.02	.400	10.2	500'/1000'	100