

Blue Jacket Cables

Blue Jacket cable provides factory floor interface to Power Limited Controls and control network devices. Often referred to as Blue Hose®, ADC's Blue Jacket is designed to be used in light industrial environments and comes in a Direct Burial and High Flex version.

PART NO.	UL/ ETL NEC TYPE	COND. (STRAND) NOM. DCR	NOMINAL CORE OD & TYPE		SHIELD MTRL NOM DCR	NOMINAL OD		NOM. IMP.	NOM. VEL. OF PROP.	NOMINAL CAPACITANCE		NOMINAL ATTENUATION		
			INCH	mm		INCH	mm			pF/FT	pF/m	MHz	dB/ 100 FT.	dB/ 100 m

78 Ohm 20 AWG Stranded (7x28) .037" TC - Foil + 55% TC Braid Shield (100% Shield Coverage) Blue SLR PVC Jacket

4-2214BE UL AWM Style 2464 300 V 80°C Allen Bradley P/N: 1770-CD Belden Equal 9463	CM CL2 	20 AWG (7x28) .037" TC 9.5Ω/M' 31.0Ω/km (Color Code:Clear, Blue)	.154 SPE	3.91	Foil + 55% TC Braid 4.1Ω/M' 13.4Ω/km	.238	6.05	78	66%	19.7	64.6	1	.6	2.0
												10	2.1	6.9
												50	3.6	11.8
												100	7.5	24.6
												200	11.0	36.1
400	16.0	52.5												

78 Ohm 20 AWG Stranded (7x28) .037" TC - Foil + 55% TC Braid Shield (100% Shield Coverage) Blue SLR LDPE Jacket

2214DB <i>Flooded Direct Burial</i> 300 V 80°C Allen Bradley P/N: 1770-CD Belden Equal 9463DB		20 AWG (7x28) .037" TC 9.5Ω/M' 31.0Ω/km (Color Code:Clear, Blue)	.154 SPE	3.91	Foil + 55% TC Braid 4.1Ω/M' 13.4Ω/km	.238	6.05	78	66%	19.7	64.6	1	.6	2.0
												10	2.1	6.9
												50	3.6	11.8
												100	7.5	24.6
												200	11.0	36.1
400	16.0	52.5												

78 Ohm 20 AWG Stranded (42x36) .037" TC - Foil + 85% TC Braid Shield (100% Shield Coverage) Blue SLR PVC Jacket

4-2224FX High Flex UL AWM Style 2464 300 V 80°C Allen Bradley P/N: 1770-CD Belden Equal 9463F	CM CL2 	20 AWG (41x36) .037" TC 9.5Ω/M' 31.0Ω/km (Color Code:Clear, Blue)	.154 SPE	3.91	Foil + 85% TC Braid 5.0Ω/M' 6.4Ω/km	.243	6.17	78	66%	19.7	64.6	1	.6	2.0
												10	2.1	6.9
												50	3.6	11.8
												100	7.5	24.6
												200	11.0	36.1
400	16.0	52.5												

78 Ohm 20 AWG Stranded (7x28) .037" TC - Foil + 85% TC Braid Shield (100% Shield Coverage) Blue SLR PVC Jacket

2224DB <i>Flooded Direct Burial</i> Allen Bradley P/N 9022B	CM CL2 	20 AWG (7x28) .037" TC 9.5Ω/M' 31.0Ω/km (Color Code:Clear, Blue)	.077 SPE	1.95	Foil + 57% TC Braid	.244	6.19	78	66%	19.7	64.6	1	.6	2.0
												10	2.1	6.9
												50	3.6	11.8
												100	7.5	24.6
												200	11.0	36.1
400	16.0	52.5												