

SECURITY ALARM CABLES



Commercial Applications CMP/FT6 Rated Unshielded



RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including UL and ETL.

| Product Description | Specifications | | Applications | Color Code Chart | | | |
|---|---------------------|---------------|--|------------------|--------------|-------------|--------------|
| Bare copper conductors, Low smoke PVC insulation, Natural low smoke PVC jacket. Sequential footage marking. | Conductor | Bare Copper | <ul style="list-style-type: none"> • Security Systems • Intercom Systems • Sound/Audio System • Power-Limited Controls | Cond | Color | Cond | Color |
| | Insulation | Low Smoke PVC | | 1 | Black | 11 | Pink |
| | 22 - 16 AWG | .009" PVC | | 2 | Red | 12 | Tan |
| | 14 - 12 AWG | .011" PVC | | 3 | White | | |
| | Jacket | Low Smoke PVC | | 4 | Green | | |
| | NEC Articles | | | 5 | Brown | | |
| 22 - 16 AWG | 725/CL2P 800/CMP | 6 | Blue | | | | |
| 14 - 12 AWG | 725 CL3P | 7 | Orange | | | | |
| Voltage Rating | | 8 | Yellow | | | | |
| 22 - 16 AWG | 300 V | 9 | Purple | | | | |
| 14 - 12 AWG | 150 V | 10 | Gray | | | | |
| Temp. Rating | 75°C | | | | | | |

| PART NO. | AWG/COND | STRAND | OUTER JKT THICKNESS | | NOMINAL OD | | AVAILABLE PUT-UPS | SHIP WT / 1M' |
|----------|----------|--------|---------------------|-----|------------|------|-------------------|---------------|
| | | | INCH | mm | INCH | mm | | |
| 932202 | 22/2 | SOL | .015 | .38 | .118 | 3.00 | 500'/1000' | 9 |
| 912202 | 22/2 | 7 | .015 | .38 | .124 | 3.15 | 500'/1000' | 10 |
| 912203 | 22/3 | 7 | .015 | .38 | .131 | 3.33 | 500'/1000' | 13 |
| 932204 | 22/4 | SOL | .015 | .38 | .136 | 3.45 | 500'/1000' | 16 |
| 912204 | 22/4 | 7 | .015 | .38 | .143 | 3.63 | 500'/1000' | 17 |
| 912206 | 22/6 | 7 | .015 | .38 | .171 | 4.34 | 500'/1000' | 24 |
| 912208 | 22/8 | 7 | .015 | .38 | .186 | 4.72 | 500'/1000' | 31 |
| 912210 | 22/10 | 7 | .015 | .38 | .218 | 5.54 | 500'/1000' | 43 |
| 912212 | 22/12 | 7 | .015 | .38 | .225 | 5.72 | 500'/1000' | 49 |
| 912002 | 20/2 | 7 | .015 | .38 | .138 | 3.51 | 500'/1000' | 14 |
| 912004 | 20/4 | 7 | .015 | .38 | .160 | 4.06 | 500'/1000' | 24 |
| 911802 | 18/2 | 7 | .015 | .38 | .157 | 3.99 | 500'/1000' | 18 |
| 911803 | 18/3 | 7 | .015 | .38 | .168 | 4.27 | 500'/1000' | 25 |
| 911804 | 18/4 | 7 | .015 | .38 | .186 | 4.72 | 500'/1000' | 36 |
| 911805 | 18/5 | 7 | .015 | .38 | .203 | 5.16 | 500'/1000' | 41 |
| 911806 | 18/6 | 7 | .015 | .38 | .222 | 5.64 | 500'/1000' | 51 |
| 911808 | 18/8 | 7 | .015 | .38 | .242 | 6.15 | 500'/1000' | 65 |
| 911809 | 18/9 | 7 | .015 | .38 | .262 | 6.65 | 500'/1000' | 68 |
| 911810 | 18/10 | 7 | .015 | .38 | .286 | 7.26 | 500'/1000' | 75 |
| 911812 | 18/12 | 7 | .015 | .38 | .296 | 7.52 | 500'/1000' | 84 |
| 911602 | 16/2 | 19 | .015 | .38 | .180 | 4.57 | 500'/1000' | 26 |
| 911603 | 16/3 | 19 | .015 | .38 | .191 | 4.85 | 500'/1000' | 38 |
| 911604 | 16/4 | 19 | .015 | .38 | .211 | 5.36 | 500'/1000' | 52 |
| 911402 | 14/2 | 19 | .015 | .38 | .222 | 5.64 | 500'/1000' | 40 |
| 911403 | 14/3 | 19 | .015 | .38 | .236 | 5.99 | 500'/1000' | 60 |
| 911404 | 14/4 | 19 | .015 | .38 | .261 | 6.63 | 500'/1000' | 73 |
| 911202 | 12/2 | 19 | .015 | .38 | .272 | 6.91 | 500'/1000' | 58 |
| 911204 | 12/4 | 19 | .018 | .46 | .308 | 7.82 | 500'/1000' | 111 |