

## Commercial Applications CMR/CMG FT4 Rated Shielded



### RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including UL and ETL.

Product Description	Specifications		Applications	Color Code Chart			
Bare copper conductors, PVC insulation, Shielded tape with drain wire, Gray PVC jacket. Sequential footage marking. <i>Shielded version has an aluminum tape and drain shielding.</i>	<b>Conductor</b>	Bare Copper	<ul style="list-style-type: none"> <li>• Security Systems</li> <li>• Intercom Systems</li> <li>• Sound/Audio System</li> <li>• Power-Limited Controls</li> </ul>	<b>Cond</b>	<b>Color</b>	<b>Cond</b>	<b>Color</b>
	<b>Insulation</b>	22 - 16 AWG .010" PVC		1	Black	11	Pink
		14 - 12 AWG .014" PVC		2	Red	12	Tan
	<b>Shield</b>	Aluminum Foil		3	White		
	<b>Jacket</b>	PVC		4	Green		
	<b>NEC Articles</b>			5	Brown		
	22 - 16 AWG	725/CL2R 800/CMR		6	Blue		
	14 - 12 AWG	725 CL3R		7	Orange		
	<b>Voltage Rating</b>	300 V		8	Yellow		
	<b>Temp. Rating</b>	75°C		9	Purple		
		10	Gray				

PART NO.	AWG/ COND	STRAND	OUTER JKT THICKNESS		NOMINAL OD		AVAILABLE PUT-UPS	SHIP WT / 1M'
			INCH	mm	INCH	mm		
8220SDGY	22/2	SOL	.015	.38	.125	3.18	500'/1000'	14
1220RSD	22/2	7	.015	.38	.130	3.30	500'/1000'	11
82204SDGY	22/4	SOL	.015	.38	.138	3.50	500'/1000'	15
12204RSD	22/4	7	.015	.38	.152	3.86	500'/1000'	19
12206RSD	22/6	7	.015	.38	.179	4.55	500'/1000'	29
12208RSD	22/8	7	.015	.38	.196	4.98	500'/1000'	32
12210RSD	22/10	7	.015	.38	.230	5.84	500'/1000'	44
12002RSD	20/2	7	.015	.38	.145	3.68	500'/1000'	16
12004RSD	20/4	7	.015	.38	.168	4.27	500'/1000'	26
11802RSD	18/2	7	.015	.38	.165	4.19	500'/1000'	22
11803RSD	18/3	7	.015	.38	.175	4.45	500'/1000'	30
11804RSD	18/4	7	.015	.38	.192	4.88	500'/1000'	37
11805RSD	18/5	7	.015	.38	.211	5.36	500'/1000'	45
11806RSD	18/6	7	.015	.38	.230	5.84	500'/1000'	61
11807RSD	18/7	7	.015	.38	.230	5.84	500'/1000'	57
11808RSD	18/8	7	.015	.38	.270	6.86	500'/1000'	64
11809RSD	18/9	7	.015	.38	.272	6.91	500'/1000'	71
11602RSD	16/2	19	.015	.38	.188	4.78	500'/1000'	32
11603RSD	16/3	19	.015	.38	.200	5.08	500'/1000'	42
11604RSD	16/4	19	.015	.38	.220	5.59	500'/1000'	58
11402RSD	14/2	19	.015	.38	.238	6.05	500'/1000'	53
11403RSD	14/3	19	.015	.38	.253	6.43	500'/1000'	66
11404RSD	14/4	19	.015	.38	.292	7.42	500'/1000'	77
11202RSD	12/2	19	.015	.38	.272	6.91	500'/1000'	67