

SECURITY ALARM CABLES



Commercial Applications CMR/CMG FT4 Rated Unshielded



RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including UL and ETL.

Product Description	Specifications	Applications	Color Code Chart				
Bare copper conductors, PVC insulation, Gray PVC jacket. Sequential footage marking.	Conductor	Bare Copper	<ul style="list-style-type: none"> • Security Systems • Intercom Systems • Sound/Audio System • Power-Limited Controls 	Cond	Color	Cond	Color
	Insulation			1	Black	11	Pink
	22 - 16 AWG	.010" PVC		2	Red	12	Tan
	14 - 12 AWG	.014" PVC		3	White		
	Jacket	PVC		4	Green		
	NEC Articles			5	Brown		
	22 - 16 AWG	725/CL2R 800/CMR		6	Blue		
14 - 12 AWG	725 CL3R	7	Orange				
Voltage Rating	300 V	8	Yellow				
Temp. Rating	75°C	9	Purple				
		10	Gray				

PART NO.	AWG/COND	STRAND	OUTER JKT THICKNESS		NOMINAL OD		AVAILABLE PUT-UPS	SHIP WT / 1M'
			INCH	mm	INCH	mm		
82202GY	22/2	SOL	.015	.38	.122	3.10	500'/1000'	9
12202R	22/2	7	.015	.38	.128	3.25	500'/1000'	10
12203R	22/3	7	.015	.38	.135	3.43	500'/1000'	13
82204GY	22/4	SOL	.015	.38	.141	3.58	500'/1000'	16
12204R	22/4	7	.015	.38	.148	3.76	500'/1000'	16
12206R	22/6	7	.015	.38	.177	4.50	500'/1000'	27
12208R	22/8	7	.015	.38	.192	4.88	500'/1000'	30
12210R	22/10	7	.015	.38	.226	5.74	500'/1000'	41
12212R	22/12	7	.015	.38	.233	5.92	500'/1000'	47
12002R	20/2	7	.015	.38	.142	3.61	500'/1000'	13
12004R	20/4	7	.015	.38	.165	4.19	500'/1000'	23
11802R	18/2	7	.015	.38	.161	4.09	500'/1000'	18
11803R	18/3	7	.015	.38	.171	4.34	500'/1000'	23
11804R	18/4	7	.015	.38	.188	4.78	500'/1000'	32
11805R	18/5	7	.015	.38	.207	5.26	500'/1000'	39
11806R	18/6	7	.015	.38	.226	5.74	500'/1000'	56
11807R	18/7	7	.015	.38	.226	5.74	500'/1000'	52
11808R	18/8	7	.015	.38	.248	6.30	500'/1000'	59
11809R	18/9	7	.015	.38	.269	6.83	500'/1000'	66
11810R	18/10	7	.015	.38	.294	7.47	500'/1000'	74
11812R	18/12	7	.015	.38	.314	7.98	500'/1000'	90
11602R	16/2	19	.015	.38	.184	4.67	500'/1000'	25
11603R	16/3	19	.015	.38	.196	4.98	500'/1000'	38
11604R	16/4	19	.015	.38	.216	5.49	500'/1000'	51
11402R	14/2	19	.015	.38	.234	5.94	500'/1000'	39
11403R	14/3	19	.015	.38	.249	6.32	500'/1000'	56
11404R	14/4	19	.015	.38	.276	7.01	500'/1000'	73
11202R	12/2	19	.015	.38	.268	6.81	500'/1000'	57